



# Sun Control Window Films


## Performance Results: Visible

Light Transmitted Total Solar	33%
Energy Rejected UV Light Rejected	61%
Glare Reduction	99%
Visible Light Reflected Interior	63%
Visible Light Reflected Exterior	19%
	29%



## Affinity 30

Enhancing light as only 3M can



Sample Area Diecut

### Affinity 30 Benefits:

- High heat rejection provides energy savings and improved comfort
- Reduces fading and helps to protect furnishings
- Lower interior and exterior reflectivity
- Reduces glare and eye discomfort
- Comprehensive 3M manufacturer's warranty
- Increases personal safety from flying glass

Glass Type (All 1/4")	Single Pane Clear	Single Pane Tinted	Double Pane Clear	Double Pane Tinted
Visible light Transmitted	33%	20%	30%	18%
Total Solar Energy Rejected	61%	63%	54%	64%
UV Light Rejected	99%	99%	99%	99%
Glare Reduction	63%	62%	62%	62%
Visible Light Reflected Int.	19%	19%	20%	20%
Visible Light Reflected Ext.	29%	14%	32%	15%
Shading Coefficient	0.45	0.42	0.53	0.41
Emissivity	0.67	0.67	0.67	0.67
U value	0.94	0.94	0.45	0.45
Solar Heat Reduction	52%	42%	35%	31%

### Solar Tint

5050 Montgomery Rd  
Cincinnati, OH 45212  
Tel: 1-888-616-1488



888.616.1488

info@solartint.com

solartint.com

st.graphics



info@st.graphics